



Jazzy[®]

SELECT 6

The Jazzy Select[®] 6 provides maximum front stability combined with the advantages of in-line motor technology. Active-Trac[®] Suspension and 6" front and rear castors offer superior performance indoors and out. An impressive selection of standard convenience features make it the easiest power chair to use.



Pride[®]
Mobility Products
Australia Pty. Ltd.
— LIVE YOUR BEST —

SPECIFICATIONS

| | |
|---|---|
| Weight capacity | Up to 136 kg (300 lbs.) |
| Maximum speed¹ | Up to 6.8 km/h (4.2 mph) |
| Ground clearance | 4.445 cm (1.75") at motors and center frame |
| Turning radius² | 54.6 cm (21.5") |
| Overall length² | 90.2 cm (35.5") without front riggings |
| Overall width² | 59.7 cm (23.5") |
| Drive wheels | 25.4 cm (10") solid |
| Anti-tips | N/A |
| Castors | 15.24 cm (6") solid, front and rear mounted |
| Suspension | Active-Trac® with Mid-Wheel 6® technology |
| Drivetrain | Two-motor, Mid-Wheel 6® |
| Braking system | Intelligent braking (electronic, regenerative disc brakes) |
| Standard electronics | 40 amp, PG GC 2 controller |
| Standard seat | High-back |
| Specialty controls | N/A |
| Battery charger | Off-board, 3.5 amp |
| Per-charge range^{1,4} | Up to 20.8 km (12.92 miles) |
| Battery requirements⁵ | (2) 12 volt deep-cycle |
| Battery size (largest) | (U-1) 30-34 AH |
| Battery weight³ | 10 kg (22 lbs.) each |
| Base weight | 46.5 kg (102.5 lbs.) |
| Standard seat weight | 19 kg (42.5 lbs.) (high-back) |
| Max. seating dimensions | 46 cm x 51 cm (18" x 20") |
| Warranty | 2-year limited |

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.

- 1) Range and speed vary with user weight, terrain type, battery charge, battery condition and tyre pressure. This specification can be subject to a variance of (+ 10% or - 5%) .
- 2) Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 3) Battery weight may vary based on manufacturer.
- 4) Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4, standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities. This specification can be subject to a variance of +10%, -5%.
- 5) AGM or gel cell type required

FEATURES

- 6" castors on front & rear for maximum stability
- In-line motor technology for increased efficiency, torque and range
- Articulating rear castor beam
- Easy access charger port and circuit breaker
- Height and depth-adjustable foot platform
- Built with ease of service in mind
- 15.24 cm (6") castors on front and rear for maximum stability

OPTIONS

- Power elevating seat
- Cup holder
- Weather cover
- Rear basket
- Oxygen tank holder
- Cane/crutch holder
- Walker holder

COLOUR



Jazzy Red